

High Performance Automatic Transmission

Description

DAYAN ATF DEX III is a premium quality automatic transmission fluid based on high viscosity index mineral oils and carefully selected additives. It is blended to meet the stringent requirements of leading automotive transmission manufacturers.

Features and benefits

- Excellent shear-stability
- Dependable anti-wear and gear protection
- Exceptionally high oxidation resistance
- Friction modified

Product and environmental safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.



The DAYAN trademark is registered and protected in Iran.

Technical Data

Test	Units	Method	ATF DEX III
Colour	-	Visual	Red
Relative Density at 15°C	g/ml	ASTM D4052	0.85
Kinematic Viscosity at 100°C	mm ² /s	ASTM D445	8
Viscosity Index	-	ASTM D2270	185
Open Flash Point	°C	ASTM D92	180
Pour Point	°C	ASTM D97	-39
Daynamic Viscosity @ -40°C	mPa.s(cP)	ASTM D2983	20.000 max.

Note:

1- The Typical characteristics are given as a guide only and may vary according to latest production according to ISO.