

Heavy Duty Diesel Engine Oil

Description

DAYAN DELVAC SERIES oils use well-proven performance additives to fight wear providing reliable lubrication, consistent performance. suitable for day to day use in non-turbocharged engines.

Features and benefits

Provide reliable all-year-round performance in the applications for which they are intended.

Applications

- Moderately rated diesel engines
- Hydraulic and Transmissions

Specifications

- SAE: 20,30,40,50,60
- API: CD/SG

Product and environmental safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The DAYAN trademark is registered and protected in Iran.

Technical Data

Test	Units	Method	20	30	40	50	60
Relative Density at 15°C	g/ml	ASTM D4052	0.88	0.89	0.89	900	900
Kinematic Viscosity at 100°C	mm ² /s	ASTM D445	8.6	12	14	20	26
Viscosity Index	-	ASTM D2270	95	96	96	91	105
Total Base Number	mg KOH/g	ASTM D2896	12	12	12	12	12
Flash Point	°C	ASTM D92	220	230	230	240	240
Pour Point	°C	ASTM D5985	-18	-18	-15	-12	-12

Note:

1- The Typical characteristics are given as a guide only and may vary according to latest production according to ISO.