

Special Flushing Oil For Stationary Gas Engine Motors

Description

DAYAN FLUSHING GASMOTOR OIL formulated from high quality mineral base stock for flushing gas engine or machinery in the engine oil draining process.

Features and benefits

High detergent efficiency in removing deposits from engine system according to low viscosity characteristic.

Applications

- For cleansing the general gas engine systems
- For cleansing the industrial machinery

Suggestion : after engine oil draining, fills the crankcase or sump with Dayan Flushing Gasmotor Oil and Operates with the mild condition for 30 minutes, then completely drains the Dayan Flushing Gasmotor Oil and refills with fresh gas engine oil

Product and environmental safety

This product should not cause any health problems when used in the applications suggested. As with all products, please take care to avoid environmental contamination when disposing of this product. Used oil should be sent for reclamation/recycling or, if not possible, must be disposed of according to relevant government/authority regulations.

The DAYAN trademark is registered and protected in Iran.

Technical Data

Test	Units	Method	Flushing gasmotor oil
Appearance	-	-	Bright & Clear
Color	-	ASTM D1500	0.5
Kinematic Viscosity at 40°C	mm ² /s	ASTM D445	60
Viscosity Index	-	ASTM D2270	95
Flash Point	°C	ASTM D92	200
Pour Point	°C	ASTM D5985	-6

Note:

1- The Typical characteristics are given as a guide only and may vary according to latest production according to ISO.