

Fuel Efficient Axle Oil

Description

DAYAN MULTI VEHICLE AXLE FLUID is a synthetic multigrade final drive lubricant. It is Dayan's prime recommendation for final drives in heavy commercial vehicles.

Features and benefits

- Fuel savings and reduced emissions due to balanced viscometric and frictional characteristics.
- Superior low temperature fluidity
- Excellent thermal and oxidation stability
- Outstanding anti-wear
- Excellent temperature reduction and shear stability
- Excellent EP properties

Application

DAYAN MULTI VEHICLE AXLE FLUID is specially formulated for use in transmissions requiring gear oil of API GL-5 specification.

Specification

- API GL-5
- DIN 51517 - III

Storage and Handling

DAYAN MULTI VEHICLE AXLE FLUID is Unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standard of Industrial and personal hygiene are maintained. Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

The DAYAN trademark is registered and protected in Iran.

Technical Data

Test	Units	Method	75W-80	75W-90
Grade	-	-	75W80	75W90
Relative Density at 15°C	g/ml	ASTM D4052	0.855	0.858
Kinematic Viscosity at 40°C	mm ² /s	ASTM D445	55	99
Kinematic Viscosity at 100°C	mm ² /s	ASTM D445	9.6	15
Viscosity Index	-	ASTM D2270	150	160
Open Flash Point	°C	ASTM D92	204	196
Pour Point	°C	ASTM D5985	<-36	<-36

Note:

1- The Typical characteristics are given as a guide only and may vary according to latest production according to ISO.