

Universal Tractor Oil

Description

DAYAN AGRI UTTO SERIES are a universal API GL-4 oil for most types of farm machinery and off-road equipment .

Features and benefits

- One oil that protects engine, transmission, hydraulic and front axles
- One oil reduces inventory, saves money
- Using an advanced formulation, DAYAN AGRI UTTO reduces engine wear

Applications

- Heavy dutty offroad and tractor transmission system

Specifications

- API GL4
- Caterpillar TO2
- Allison C4
- Demision HF-0, HF-1, HF-2

Product and environmental safety

DAYAN AGRI UTTO series oils are unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standards of industrial and personal hygiene are maintained. Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

The DAYAN trademark is registered and protected in Iran.

Technical Data

Test	Units	Method	0W-20	5W-30	10W-30	15W-40	20W-50
SAE Viscosity	-	-	0W-20	5W-30	10W-30	15W-40	20W-50
Relative Density at 15°C	g/ml	ASTM D4052	0.84	0.85	0.86	0.87	0.89
Kinematic Viscosity at 40°C	mm ² /s	ASTM D445	36	66	60	112	186
Kinematic Viscosity at 100°C	mm ² /s	ASTM D445	7.4	11	9.35	15	20
Viscosity Index	-	ASTM D2270	178	159	137	140	125
Total Base Number	mg KOH/g	ASTM D2896	9	9	9	9	9
Flash Point	°C	ASTM D92	210	210	235	230	220
Pour Point	°C	ASTM D5985	-48	-39	-39	-30	-21

Note:

1- The Typical characteristics are given as a guide only and may vary according to latest production according to ISO.