

Metal Forming Oil

Description

Base oil for rolling.

Features and benefits

- Very low aromatic (0,03%) and sulfur content.
- High thermal and UV resistance.
- Narrow cut allowing processing cost reductions.

Application

- rolling non staining base stock.

Storage and Handling

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

DAYAN METAL-FORMING S 2 is Unlikely to present any significant health or safety hazard when properly used in the recommended application, and good standard of Industrial and personal hygiene are maintained. Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

The DAYAN trademark is registered and protected in Iran.

Technical Data

Test	Units	Method	Metal-Forming S 2
Appearance	-	Visual	Clear
Sulphur Content	-	ASTM D1552	Very Low
Kinematic Viscosity at 40°C	mm ² /s	ASTM D445	2.6
Pour Point	c°	ASTM D5985	<-48

Note:

1- The Typical characteristics are given as a guide only and may vary according to latest production according to ISO.