

Automatic Transmission Fluid

Description

DAYAN ATF DEX II is an Automatic Transmission Fluid which may be used in automatic transmissions and power steering units of many types of vehicles where Dexron IID or Mercon performance is required. It is also approved for use in many European heavy duty automatic transmissions and manual transmissions.

Features and benefits

- Multiple approvals provide wide ranging use.
- Ensures efficient operation of power steering units under all conditions.
- High thermal stability
- Enhanced friction characteristics and wear protection
- Effective seal compatibility reduces the risk of leakages.

Product and environmental safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

The DAYAN trademark is registered and protected in Iran.

Technical Data

Test	Units	Method	ATF DEX II
Relative Density at 15 °C	g/ml	ASTM D4052	0.86
Kinematic Viscosity at 40 °C	mm ² /s	ASTM D445	38
Kinematic Viscosity at 100°C	mm ² /s	ASTM D445	7.7
Viscosity Index	-	ASTM D2270	180
Open Flash Point	°C	ASTM D92	210
Pour Point	°C	ASTM D97	-48
NAS	-	NAS 1638	8

Note:

1- The Typical characteristics are given as a guide only and may vary according to latest production according to ISO.