

# DYN 1-262

## Two-Stroke Motorcycle Oil Additive Package



### Description

**DYN 1-262** is a low ash multifunctional additive for two-stroke oils. This product made by selected high-quality detergent, dispersant. It has a good detergency, lubricity, low ash, excellent smoke extraction and other performance.

DYN 1-262 is used to meet API TB, TC quality grade air-cooled two-stroke gasoline engine oil.

### Recommended Treat Rate

Performance Level	DYN 1-262, %wt
API TB	4.0
API TC	5.5

### Typical Characteristics

Physical & Chemical Characteristics	Specification	Test Method
Kinematic Viscosity @ 100°C , cSt	<b>97.0 Min.</b>	ASTM D445
Flash Point , °C	<b>180 Min.</b>	ASTM D92
Calcium Content , % wt	<b>0.75 - 1.00</b>	ASTM D4951
Nitrogen Content , % wt	<b>0.71 - 1.00</b>	ASTM D5762
Total Base Number , mg KOH/g	<b>35 - 48</b>	ASTM D2896
Density @ 20°C	<b>885 - 925</b>	ASTM D4052

### Packing And Handling

**DYN 1-262** is packed in metal drums and is normally handled at room temperature. The following storage and handling temperatures are recommended:

Storage Handling temperature should not exceed 50 °C (122 °F).

And blending temperature should not exceed 60 °C (140 °F).

For more extensive information on the safe handling and use of this product, see the Material Safety Data Sheet.