

Heavy Duty Diesel Engine Oil

Description

DAYAN DELVAC CG-4 40 oil use well-proven performance additives to fight wear providing reliable lubrication, consistent performance. suitable for day to day use in non-turbocharged engines.

Features and benefits

- Monograde
- High viscosity index
- High detergent level
- High dispersancy level
- Good anti-wear, anti-corrosion properties
- Good anti-rust, anti-oxidant, anti-foaming properties.

Applications

- All diesel turbocharged or normally aspirated engines.

Specifications

- SAE: 40
- API: CG-4

Product and environmental safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The DAYAN trademark is registered and protected in Iran.

Technical Data

Test	Units	Method	DELVAC CG-4 40
Base Oil Type	-	-	Mineral
Relative Density at 15°C	g/ml	ASTM D4052	0.89
Kinematic Viscosity at 100°C	mm ² /s	ASTM D445	14.4
Viscosity Index	-	ASTM D2270	96
Total Base Number	mg KOH/g	ASTM D2896	8
Flash Point	°C	ASTM D92	230
Pour Point	°C	ASTM D5985	-18

Note:

- 1- The Typical characteristics are given as a guide only and may vary according to latest production according to ISO.