

Advanced Multipurpose Grease

Description

DAYAN GREASE LI-CA 1029 is a fluid grease for use in centralised lubrication systems. This grease is based on highly refined mineral as well as selected synthetic base oils, extreme-pressure and other carefully selected additives to provide excellent protection in all conditions.

Features and benefits

- Good water resistance
- Effective extreme-pressure properties
- Good pumpability

Applications

- Pneumatic tools.
- Centralised chassis lubrication systems on trucks and buses or other "one-shot" systems.

Storage and Handling

Proper standards of storage and handling are necessary with all lubricants, and are particularly vital with greases. Packages should be treated with care at all stage, to prevent contamination of their contents and damage to containers. All packages should be stored indoors; where outside storage is unavoidable, they should be covered to avoid the possible ingress of water and the consequent obliteration of painted markings Greases should not be exposed to extremes of temperature nor to direct hot sunlight.

The DAYAN trademark is registered and protected in Iran.

Technical Data

Test	Units	Method	LI - CA 1029
NLGI Consistency	-	-	00/000
Soap Type	-	-	Lithium Calcium
Base Oil	-	-	Semi synthetic
Color	-	ASTM D1500	Red
Kinematic Viscosity at 40°C	cSt	ASTM D445	60
(4-ball) welding point	Kgf	ASTM D2596	250
Temperature Range (temporally)	-	-	-40/+120

Note:

- 1- The Typical characteristics are given as a guide only and may vary according to latest production according to ISO.